Version : N°1 (12/11/2015) Newell Rubbermaid UK Limited

#### **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 1/10

Revision: N°3 (12/11/2015)

## **SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: SHARPIE BLACK INK

Product code: PR1007.

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Ink for SHARPIE: Pro King Size

#### 1.3. Details of the supplier of the safety data sheet

Registered company name: Newell Rubbermaid UK Limited.

Address: Halifax Ave - Fradley Park. WS 13 8SS. Lichfield Staffordshire. United Kingdom.

$$\label{eq:first-energy} \begin{split} & Telephone: +44~(0)~1543447001. \quad Fax:. \\ & Aftersales. SERVICE@newellco.com \end{split}$$

www.newellrubbermaid.com

## 1.4. Emergency telephone number: 0845 4647.

Association/Organisation: National Poisons Information Service.

#### **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

## In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

## 2.2. Label elements

## In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:







GHS07

GHS05

(

Signal Word:

DANGER

Product identifiers:

603-003-00-0 PROPAN-1-OL 603-004-00-6 N-BUTANOL

EC 207-396-6 C.I. SOLVENT VIOLET 9

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

Version: N°1 (12/11/2015) Newell Rubbermaid UK Limited

#### SHARPIE BLACK INK - PR1007

Date: 12/11/2015 Page 2/10

Revision: N°3 (12/11/2015)

H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P240 Ground/bond container and receiving equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response:

P302 + P352 IF ON SKIN: Wash with plenty of water/...

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...
P312 Call a POISON CENTER/doctor/.../if you feel unwell.

P321 Specific treatment (see ... on this label).

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use... to extinguish.

Precautionary statements - Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary statements - Disposal:

P501 Dispose of contents/container to ...

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

**Composition:** 

C 0111-P 05111011 1			
Identification	(EC) 1272/2008	Note	%
INDEX: 603-003-00-0	GHS02, GHS05, GHS07	[1]	25 <= x % < 50
CAS: 71-23-8	Dgr		
EC: 200-746-9	Flam. Liq. 2, H225		
	Eye Dam. 1, H318		
PROPAN-1-OL	STOT SE 3, H336		

Version : N°1 (12/11/2015) Newell Rubbermaid UK Limited

#### **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 3/10

Revision: N°3 (12/11/2015)

INDEX: 603-004-00-6	GHS02, GHS05, GHS07	[1]	10 <= x % < 25
CAS: 71-36-3	Dgr		
EC: 200-751-6	Flam. Liq. 3, H226		
	Acute Tox. 4, H302		
N-BUTANOL	STOT SE 3, H335		
	Skin Irrit. 2, H315		
	Eye Dam. 1, H318		
	STOT SE 3, H336		
INDEX: 603-016-00-1	GHS07	[1]	10 <= x % < 25
CAS: 123-42-2	Wng		
EC: 204-626-7	Eye Irrit. 2, H319		
DIACETONE ALCOHOL			
CAS: 467-63-0	GHS05, GHS09		0 <= x % < 2.5
EC: 207-396-6	Dgr		
	Eye Dam. 1, H318		
C.I. SOLVENT VIOLET 9	Aquatic Acute 1, H400		
	M Acute = 1		
	Aquatic Chronic 1, H410		
	M Chronic = 1		

#### Information on ingredients:

[1] Substance for which maximum workplace exposure limits are available.

#### **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. Description of first aid measures

## In the event of exposure by inhalation:

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

## In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

## In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

#### In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Seek medical attention immediately, showing the label.

## 4.2. Most important symptoms and effects, both acute and delayed

No data available.

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

Version: N°1 (12/11/2015) Newell Rubbermaid UK Limited

#### **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 4/10

Revision: N°3 (12/11/2015)

## **SECTION 5: FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

#### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

Prevent the effluent of fire-fighting measures from entering drains or waterways.

## 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)
- sulphur dioxide (SO2)

### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

### For non first aid worker

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

## For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

#### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

## 6.4. Reference to other sections

No data available.

## **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Remove contaminated clothing and protective equipment before entering eating areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Version : N°1 (12/11/2015) Newell Rubbermaid UK Limited

#### **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 5/10

Revision: N°3 (12/11/2015)

## Fire prevention:

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

## Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid eye contact with this mixture at all times.

### Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

## Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

## **Packaging**

CAS

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

VME:

# **8.1.** Control parameters

## Occupational exposure limits:

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria
71-23-8	200 ppm	400 ppm	-	-	-
71-36-3	20 ppm	-	-	-	-
123-42-2	50 ppm	-	-	-	-
- Germany - AGW (BA	uA - TRGS 900	, 21/06/2010):			

VME:

Excess

Notes

#### **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 6/10

Revision: N°3 (12/11/2015)

71-36-3	100 ml/m3	310 mg/m3	1(I)	DFG, Y		
123-42-2	20 ml/m3	96 mg/m3	2(I)	DFG, H		
- France (INRS - E	D984 :2008) :					
CAS	VME-ppm:	VME-mg/m3	: VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
71-23-8	200	500	-	-	-	84
71-36-3	-	-	50	150	-	84
123-42-2	50	240	-	-	-	84
- UK / WEL (Work	place exposure lim	its, EH40/2005,	2007):			
CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:	
71-23-8	200 ppm	250 ppm	-	-	-	
71-36-3	-	50 ppm	-	-	-	
123-42-2	50 ppm	75 ppm	-	-	-	

#### 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Recommended properties:

- Impervious gloves in accordance with standard EN374

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Version: N°1 (12/11/2015) Newell Rubbermaid UK Limited

#### **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 7/10

Revision: N°3 (12/11/2015)

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- A1 (Brown)

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### 9.1. Information on basic physical and chemical properties

**General information:** 

Physical state: Fluid liquid.

Important health, safety and environmental information

pH: Not relevant. Not relevant. Boiling point/boiling range: 28.00 °C. Flash Point: Vapour pressure (50°C): Not relevant. Density: Not stated. Water solubility: Insoluble. Melting point/melting range: Not relevant. Self-ignition temperature: Not relevant. Decomposition point/decomposition range: Not relevant.

## 9.2. Other information

No data available.

## **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

No data available.

## 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

## 10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

#### 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)
- sulphur dioxide (SO2)

Version: N°1 (12/11/2015) Newell Rubbermaid UK Limited

#### **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 8/10

Revision: N°3 (12/11/2015)

## **SECTION 11: TOXICOLOGICAL INFORMATION**

### 11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

#### 11.1.1. Substances

#### Acute toxicity:

C.I. SOLVENT VIOLET 9 (CAS: 467-63-0)

Oral route:

LD50 > 5000 mg/kg Species : Rat

#### 11.1.2. Mixture

No toxicological data available for the mixture.

#### **SECTION 12: ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

## 12.1. Toxicity

#### **12.1.2.** Mixtures

No aquatic toxicity data available for the mixture.

## 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

## 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

No data available.

## 12.6. Other adverse effects

No data available.

## German regulations concerning the classification of hazards for water (WGK):

WGK 2 (VwVwS vom 27/07/2005, KBws): Hazardous for water.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

Version : N°1 (12/11/2015) Newell Rubbermaid UK Limited

## **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 9/10

Revision: N°3 (12/11/2015)

#### Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

#### **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

#### 14.1. UN number

1993

#### 14.2. UN proper shipping name

UN1993=FLAMMABLE LIQUID, N.O.S.

## 14.3. Transport hazard class(es)

- Classification:



3

## 14.4. Packing group

Ш

#### 14.5. Environmental hazards

## 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	274 601 640E	E1	3	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	III	5 L	F-E.S-E	223 274 955	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3	E1
	3	-	III	Y344	10 L	-	-	A3	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

## **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.

Version : N°1 (12/11/2015) Newell Rubbermaid UK Limited

#### **SHARPIE BLACK INK - PR1007**

Date: 12/11/2015 Page 10/10

Revision: N°3 (12/11/2015)

- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

#### - Container information:

The mixture is contained in packaging that does not exceed 125 ml.

#### - Particular provisions:

No data available.

## - German regulations concerning the classification of hazards for water (WGK) :

WGK 2 (VwVwS vom 27/07/2005, KBws): Hazardous for water.

#### 15.2. Chemical safety assessment

No data available.

#### **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### Wording of the phrases mentioned in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### Abbreviations:

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame
GHS05 : Corrosion

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.